

QUICK REFERENCE CHART

PRODUCT	DIMENSIONS			SPLICE CAPACITY	FEEDER / DROP DENSITY	SC-APC ADAPTER PORT	CONFIGURATION	APPLICATION	ENVIRONMENTAL SEALING	TEST STANDARDS	GROUNDING	HARD-ENED OPTION	SPLITTERS	CABLE DIAMETER RANGE	PALLET QTY
G5NT 	Internal Diameter 5" Height 11"	(127mm) (279.4mm)		72F (single stacked) 144F (double stacked) 192F (mass fusion)	1 Main Oval Port 12 Drop Ports	16	Butt Splice	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm)	96
G5NB 	Internal Diameter 5" Height 11"	(127mm) (279.4mm)		72F (single stacked) 144F (double stacked) 192F (mass fusion)	1 Main Oval Port 8 Drop Ports 1 Branch Port	16	Butt Splice	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	96
G6N 	Internal Diameter 6" Height 15"	(152.4mm) (381.0mm)		108F (single stacked) 216F (double stacked)	1 Main Oval Port 16 Drop Ports 1 Branch Port	16	Butt Splice	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - optional (requires 1 drop port)	Yes	PLC Type 60mm x 7mm x 4mm 6 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	30
G9 	Internal Diameter 9" Height 20"	(228.6mm) (101.6mm)		144F (single stacked) 288F (double stacked)	1 Main Oval Port 16 Drop Ports 2 Branch Ports 1 Ground Port	16	Butt Splice	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Optional bond strap and clips available	Yes		Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	16
YELLOWJACKET 	External Width 16.0" Height 8.75" Depth 5.75"	(101.6mm) (101.6mm) (101.6mm)		72F (single stacked) 144F (double stacked) 192F (mass fusion)	4 Main Cable Ports 16 Drop Ports	16	Butt Splice Aerial Terminal	Aerial Strand Pedestal	Dust Resistant Moisture Resistant	Telcordia GR771 Core IP65 IEC 61300	Yes - Optional bond strap and clips available	Yes 8 ports max	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.1 - 0.9 " (2.54 - 22.86mm) Drop 0.062 - 0.19" (1.5748 - 4.826mm)	108

All specifications subject to change without notice. © 2023 Channell Commercial Corporation. All rights reserved.